



Providing Value For...

- **Companies** of all sizes promoting wellness to improve the health of employees and reduce health care costs
- **Pharmacies** as a community service enhancing professional image, prescription business and customer loyalty
- **Hospital outpatient clinics**, busy **doctors offices** and **dental practices** to obtain accurate and reliable vital sign readings with minimal staff assistance
- **Fitness centers** to provide a valuable and popular member service before and after workouts
- **Community outreach programs**
- **Senior centers**, retirement communities, and anywhere people gather

Features

- ✓ Blood pressure, pulse rate and weight
- ✓ Built-in Printer
- ✓ Data retention and graphical trend charts
- ✓ Data available in personal health record on www.LifeClinic.com (some locations)
- ✓ Easy-to-read computer display
- ✓ Oscillometric methodology
- ✓ Information is updated regularly
- ✓ Body Mass Index option

Model 90557

Vital Signs Monitoring System Specifications

Accuracy:	Complies with AAMI (Association for the Advancement of Medical Instrumentation) Standards
CRT Display with Touchscreen::	14" graphical color display for easy interaction and operation
Temperature:	
Operating:	50 to 104° F (10 to 40° C)
Storage:	-40 to 131° F (-40 to 55° C)
Humidity:	10 to 95% (noncondensing)
Weight Measurement::	
Range:	40-300 lbs.
Accuracy:	+/- 1 lbs.
Measurement Range:	Systolic: +50 to +260 mmHg Diastolic: +30 to +240 mmHg Method: Oscillometric Pulse: 40 bpm - 199 bpm
Connectivity::	RJ45 Ethernet, Analog Phone
Printer:	
Resolution:	200 DPI (8 dots/mm)
Paper:	4.38 in. (112mm) wide, 100m or 25m long
Loading:	Easy front-loading paper cabinet
Overpressure Limit:	310 +/- 10 mmHg
Test Time:	Typically one to three minutes
Physical Dimensions:	
Height:	70.5 in (179.1 cm)
Width:	41 in (104.1 cm)
Depth:	25 in (63.5 cm)
Weight:	Approximately 260 lbs.
Input Power Requirements:	110-120 VAC, 57-63 Hz, 4 Amps 220-240 VAC, 47-53 Hz, 1 Amp 3-wire grounded outlet
Special Options:	Display board for health information or promotional material
Regulatory/Safety:	ETL and CSA Listed, UL2601 C22.2 No. 601.1
EMC:	FCC Part 15, IEC 60601-1-2